



## **SAFECRAFT 5015 Safety Harness Installation Guide**


The SAFECRAFT 5015 Safety Harness is designed with many features to aid the ease of usage: from our innovative pull-down tang-adjuster, state-of-the-art aluminum adjusters, and advanced webbing. Each harness is hand-assembled in the USA by craftsman, with attention to detail. For detailed descriptions and installation tips, please visit our website at [www.safecraftracing.com](http://www.safecraftracing.com).

**It is essential that all 2-inch belts be installed correctly. This applies to lap belts, shoulder belts and sub belts.**


**Please follow the instructions, which shows how to lock the webbing into the “three bar adjusters”.**

**Do not allow any ID tags (SFI, FIA or Warning) to be left threaded into the “three bar adjusters”. Make sure that all ID tags pass completely through the adjusters.**


**2-INCH BELTS DO NOT REQUIRE THAT THE WEBBING BE FOLDED TO GO THROUGH A BOLT PLATE OR WRAP AROUND A BAR.**




Step 1:  
Insert webbing  
through the 3-bar  
adjuster.



Step 2:  
Pull webbing to 8-10  
inches beyond  
adjuster and insert  
into mount  
brackets.



Step 3:  
Fold back webbing  
and re-insert through  
the 3-bar adjuster as  
shown.



Step 4:  
Fold back webbing  
again and insert  
through bottom  
portion of buckle.

Please refer to [www.FIA.com](http://www.FIA.com) for the most up-to-date Safety Harness Installation Guidelines.

For any questions or assistance, please call (+1)813-758-3571 OR Contact us at [info@safecraftracing.com](mailto:info@safecraftracing.com).